










Carbon Steel Open Head 10-Gallon Drum Specification

Press  to see Check List only.

Description	Package ID Number	Packaging Filling Instructions *
Drum, Carbon steel, open head, 10 gallon, 13-7/8 in. ID, UN 1A2/X 70/S ; UN 1A2/Y 1.2/100 , 0.9119 mm Nominal (20 gauge)	112-6215	CHK-13 (for Hazmat use) or PKG-03 (for Type A use)

Mfg. Details Per: DOE Packaging Specifications
No. 1A2-100-00
Issue Date: February 1, 2000
Revised Date:

	1.0 GENERAL DESCRIPTION
	2.0 MATERIAL DETAILS
	3.0 CONTAINER PERFORMANCE CRITERIA
	4.0 QUALITY ASSURANCE
	5.0 MARKING
	6.0 INTENDED USE
	7.0 SUGGESTED MANUFACTURERS
	8.0 AUTHORIZED CHANGES
	9.0 DISTRIBUTION OF UN PERFORMANCE TEST REPORTS (per ¶ 3.1)

* For future use.

Company
Name
Here

Packaging Specifications

Open Head Carbon Steel Drum

Specification No. 1A2-100-00

Issued: February 1, 2000

Revised:

Page 1 of 7

1.0 GENERAL DESCRIPTION

Open Head (OH) Carbon Steel drum with welded seams, 2 or 3 rolling hoops, steel body, steel head, conventional (with seams) construction. Steel gauge and specific variations as specified in [Appendix A-1](#) for 55, 30, 15 or 16, 10, 5 gallon drum capacity.

1.1 United Nations Designation - UN 1A2 /X **/ S/ * [UN 1A2 /Y sg/ tp/ *]^{dm} [per 49 CFR, §178.503]

- dm** = Drum dual marked for liquids, as well as solid material.
- 1A2** = Open head steel drum.
- X** = Suitable for Packing Group I, II, and III materials; Y = PG II and III only.
- **** = Maximum allowable gross weight in kilograms for which the drum was tested .
- S** = Designation indicates packaging is for solid materials [or combination packaging].
- *** = The last two (2) digits of the calendar year in which the container was manufactured.
- sg** = Specific Gravity of material for which drum design type was tested.
- tp** = Hydrostatic test pressure (in kilopascals) for which drum design type was tested. [100 kPa = 14.7 psig; 250 kPa = 36.3 psig]

Specific UN Markings are specified in the Purchase Order Description for the referenced package ID number for each specific drum, which are the Company minimum UN requirements.

1.2 Size:

Inside diameter (in inches) [as specified in the Purchase Order Description for the referenced package ID number].

Drum dimensions to be in accordance with ANSI MH2-1997 Standards (American National Standards Institute) for Steel Drums and Pails *[does not apply to 15 and 5 gallon drums]*.

2.0 MATERIAL DETAIL

Drum construction must comply with Title 49, Code of Federal Regulations (49 CFR), §178.504 (latest edition) for steel drums, and the following minimum requirements. Manufacturer shall document appropriate quality control on incoming raw material. No significant changes to the manufacturing process or raw material is allowed without prior approval of the Company. Steel thickness dimensions/tolerances in conformance with TABLE, per [Appendix A-1](#).

2.1 Drum Body:

Cold rolled steel, ASTM A 366 or equivalent. Top of body rolled to form inch false wire--see [Appendix A-1](#) for steel size for stated drum capacity.

2.2 Drum Head:

Cold rolled steel, ASTM A 366 or equivalent; see [Appendix A-1](#) for steel size.

2.3 Drum Bottom:

Cold rolled steel, ASTM A 366 or equivalent; same steel as drum body.

Open Head Carbon Steel Drum

Specification No. 1A2-100-00

Issued: February 1, 2000

Revised:

Page 2 of 7

2.4 Body Seams:

Welded (on-line, continuous welder).

2.5 Chimes:

Mechanically seamed; bottom chime triple seamed, or either double-seamed or double-seamed *and* welded, if the double seam drum meets UN test criteria as specified.

2.6 Gasket:

Closed-cell rubber, glued into lid--gasket material and size as necessary to meet UN performance tests. Gasket to have an operating range of -40°F to +158°F. Must be EPDM or approved equivalent.

2.7 Rolling Hoops:

Three (3) each separate rolling hoops formed into the drum body, with one not more than three (3) inches from top drum curl for 55-gallon capacity and larger. Two (each) rolling hoops for under 55-gallon capacity (5-gallon called beads). Rolling hoops to be in accordance with ANSI MH2-1997 Standards.

2.8 Closure:

Twelve (12) gauge bolt type locking ring, welded lugs, one lug threaded, with steel bolt. Locking ring painted, coated, or galvanized to prevent corrosion. See [Appendix A-1](#) for minimum required bolt sizes.

Manufacturer/ supplier must furnish the Company, in writing, closure requirements, as performed for the UN design test; per 49 CFR, §178.2(c)(1). Ref: §9.0 for distribution.

2.9 Surface Preparation:

Surfaces shall be prepared to retard rust formation, or be sufficiently cleaned for application of interior and exterior coatings.

2.10 Interior finish:

55 and 30 gal: Lined with Morton Series 46, 2/3 Epoxy, 1/3 Phenolic coating, 1 mil. [*or an equivalent material, after approval by the Company*]

5, 10, and 15 gal: Lined with clear phenolic coating, 1/10 mil, or equal, for rust prevention.

2.11 Exterior finish:

Body painted SSCI (Steel Shipping Container Institute) Black, with White head (*unless specified differently elsewhere*).

2.12 Seaming Compound:

Bottom chime must be sealed with a seaming compound, and applied in conformance to standard manufacturing quality procedures, to ensure no leakage/seepage. Seaming compound is omitted for double seam/welded bottom chimes.

2.13 Cleanliness:

Finished drums must be free of rust, dirt, oil, solvents, metal shavings, foreign contaminants, and interior moisture.

3.0 CONTAINER PERFORMANCE CRITERIA

Manufacturer shall successfully test and certify that containers meet or exceed the requirements of 49 CFR, §178.600 - 178.608; Packing Group I level for solids, Packing Group II level for liquids.

3.1 Performance Test Documentation:

Upon request, the manufacturer must be capable of providing copies of the performance test documentation for purchased packagings, as required by 49 CFR, §178.601(l) for the UN certification marked packaging. Periodic audit copies will be requested randomly on purchased UN packagings. Ref: §9.0

Open Head Carbon Steel Drum

Specification No. 1A2-100-00

Issued: February 1, 2000

Revised:

Page 3 of 7

3.2 Performance Tests:

The specified drums require the **U.S. Department of Transportation** UN performance criteria for design qualification testing, periodic retesting, and production tests established in 49 CFR, ¶178.600 - 178.608:

NOTE TO SELLER: The UN test/marketing certifications must be made by the drum manufacturer or a Department of Transportation approved third-party tester.

4.0 QUALITY ASSURANCE

The Seller shall assure, and be responsible, that the quality of the drums furnished under this document are of good quality, as pursuant to industry standard manufacturing practices for steel drums, including the materials/components used in the manufacturing of the stated steel drums.

The Seller shall meet the requirements stipulated in this document, and the specific requirements of the Purchase Order Description for the specific drum as specified in the Purchase Order .

4.1 Manufacturer's Certification:

By the act of placing the UN performance criteria markings on each drum purchased, the manufacturer acknowledges he has certified, and accepted responsibility, that the stated drum design meets or exceeds the U.S. Department of Transportation's UN performance requirements as stipulated in ¶3.2 of this document, and in accordance with the markings prescribed in 49 CFR, ¶178.503.

In addition, this certification marking acknowledges that the drum manufacturer has complied with the specific standards for steel drums specifically listed in 49 CFR ¶178.504.

4.2 Receiver Inspections:

The following inspections will be performed on the incoming drums by a Company designee to determine the drums meet quality standards and the requirements of this document. However, the Company is not limited to the following inspections to determine quality and specification conformance. Conformance will be indicated by a Y or N in the "Y/N" column, and negative responses documented and processed through the Company's Quality Assurance Program.

NOTE: Checklist for this specification is on following page.

Open Head Carbon Steel Drum

Specification No. 1A2-100-00

Issued: February 1, 2000

Revised:

Page 4 of 7

This checklist is to be reproduced for QC Inspections.

Receiver Inspection Quality Control (QC) Checklist for Incoming Steel Drums

QC Conformance		Y/N	<< "No's" to be documented in accordance with the Company's QA Program.
1	Steel gauge size (Appendix A-1)		Meets dimensions/tolerances per attached GAUGE TABLE, Appendix A-1 .
2	Capacity (¶1.0)		Drum is the capacity specified in the Order/Purchase Order Description.
3	Drum Surface (¶2.9, 2.10, 2.11)		Clean, no significant scratching, dings or dents in drum; no significant corrosion, on exterior and interior surface of drum.
4	Locking rings, chimes (¶2.8, 2.5)		Bolted locking rings are painted steel, contain bolt size (minimum) specified in Appendix A-1 , and show no significant rusting /corrosion.
			Bolted locking rings close tightly; not loose around drum lid.
5	Drum lids (¶2.11)		Lids are painted WHITE; no significant rusting/corrosion or dents.
6	Gaskets in lids (¶2.6)		Gaskets are securely glued into the drum lids.
7	Drum interior (¶2.10)		Visually verify lined, including lids; ref. ¶2.10 of this specification.
8	Drum exterior (¶2.11)		Painted Black (SSCI {Steel Shipping Container Institute} standard), except lids, unless another color is specified elsewhere in the specific order.
9	Markings (¶5.0)		Drums marked (as a minimum) with specified UN markings, per Purchase Order Description – which include BOTH solid and liquid (dual) UN markings.
			Drums legibly marked (embossed) on drum bottom in accordance with required 49 CFR markings, and specified gross test weight. Permanent (embossed) markings are not required on bottoms of 5 and 10 gallon drums—required durable complete markings must be on bottom or side per 49 CFR, ¶178.503(a).
			Markings include the manufacturer's identification – company name or registered symbol (initials or M-number), or test agency code; after USA/. Ref: 49 CFR ¶178.503(a)(8).
11	Side Markings (¶5.0)		The required UN markings (including the specified dual UN marks) are durably and legibly marked on side.

Package ID Number_____

P. O. Number_____

Total Units Received_____

Inspection Method: Per Company's QC Inspection Program

Sample Size_____ [Based on ANSI/ASQC Z1.4-1993]

Non-Conformance Document No. _____

Inspector/Date_____

Additional comments on back: _____check, if yes.

The above QC inspection check list shall be accomplished for each order based on random samples of incoming carbon steel drums by QC personnel to determine manufacturer's conformance to these specified Packaging Specifications.

Shipments of carbon steel drums not meeting specified requirements will be returned to the seller for credit.

QC inspections resulting in noncompliance with Packaging Specifications is cause for rejection of the entire shipment.

Open Head Carbon Steel Drum

Specification No. 1A2-100-00

Issued: February 1, 2000

Revised:

Page 5 of 7

5.0 MARKING

As a minimum, each drum shall be marked in accordance with 49 CFR, §§178.3, 178.502 and 178.503 in a conspicuous location on exterior surface of the drum. Duplicate markings must be on drum sides, just below top drum curl, to be in compliance with §178.3(a)(5). Markings shall have a minimum letter height of 1/2-inch. Markings must include the manufacturer's identification – company name or registered symbol (initials or M-number), or test agency code, per 49 CFR §178.503(a)(8).

Open Head Drums are to be UN dual marked (embossed) for both liquids and solid materials.

Additionally, drums are to be marked with the UN markings, including the specified dual markings, as stipulated in §1.1. of this specification, and specifically stated in the Purchase Order Description.

The letters: CATN--(dash) plus the last four (4) numbers of the package ID number must be marked below the UN markings:

55 gal	=	CATN--6400
30 gal	=	CATN--6330
15 gal	=	CATN--6225
10 gal OH	=	CATN--6215
5 gal OH	=	CATN--6210

6.0 INTENDED USE

Containers are intended for Packing Group II and III hazardous materials in liquid form and PG I in **solid** form. Maximum fill capacity of the drum shall not exceed the tested gross weight or density marked.

7.0 SUGGESTED MANUFACTURERS

The following list of suggested manufacturers have demonstrated ability to comply to the requirements set forth in this document. However this list does not guarantee current or continued availability as a suggested manufacturer source:

[Enter Suggested Manufacturer\(s\) Here:](#)

The Seller must advise the Company prior to any change in the current source (manufacturer) of packaging materials described in these Packaging Specifications.

Any Manufacturer that satisfactorily demonstrates to the Company the capability to furnish packaging in compliance with these Packaging Specifications, may be added to the above listing.

Open Head Carbon Steel Drum

Specification No. 1A2-100-00

Issued: February 1, 2000

Revised:

Page 6 of 7

8.0 AUTHORIZED CHANGES

Changes/revisions in the requirements specified in this document will only be authorized by the Company.

9.0 DISTRIBUTION OF UN PERFORMANCE TEST REPORTS (per ¶3.1) and CLOSURE INSTRUCTIONS (per ¶2.8)

Closure Instructions must be furnished for each initial order, and annually (at the minimum) for each type/size package purchased by the Company to the address below.

Upon specific request, UN performance test documentation for specified order/shipment will be submitted directly to:

COMPANY NAME AND ADDRESS (enter information below)

**SPECIFIC REQUIREMENTS for
UN PACKAGING SPECIFICATIONS**

APPENDIX A-1

Issued/Revised: February 1, 2000

CARBON STEEL DRUM CONSTRUCTION VARIATIONS

OPEN HEAD (OH) DRUMS <i>[Fully Removable Heads]</i>								TIGHT HEAD DRUMS		
<i>No. 1A2-104-00</i>			<i>No. 1A2-100-00</i>					<i>No. 1A1-101-00</i>		
Construction	110 gallon	85 gallon	55 gallon	30 gallon	15/16 gallon	10 gallon	5 gallon	55 gallon	30 gallon	16 gallon
Nominal, mm	1.5189	1.5189	1.5189	1.2141	0.9119	0.9119	0.7595	1.2141	1.2141	0.9119
** Steel Thickness	.0598 in.	.0598 in.	.0598 in.	.0478 in	.0359 in.	.0359 in.	.0299 in.	.0478 in.	.0478 in.	.0359 in.
Minimum, mm	1.3538	1.3538	1.3538	1.0871	0.8230	0.8230	0.6833	1.0871	1.0871	0.8230
<i>Drum gauge</i>	.0533 in	.0533 in.	.0533 in.	.0428 in.	.0324 in	.0324 in	.0269 in.	.0428 in.	.0428 in.	.0324 in
	16 ga.	16 ga.	16 ga.	18 ga.	20 ga.	20 ga.	22 ga.	18 ga.	18 ga.	20 ga.
Head Thickness	1.5189	1.5189	1.5189	1.2141	0.9119	0.9119	0.7595	1.2141	1.2141	0.9119
Same Tolerances	16 ga.	16 ga.	16 ga.	18 ga.	20 ga.	20 ga.	22 ga.	18 ga.	18 ga.	20 ga.
Rolling Hoops	3 each	3 each	3 each	2 each	2 each	2 each	2 beads	2 each	2 each	2 each
Locking Ring –mm	2.6568	2.6568	2.6568	2.6568	1.5189	1.5189	0.9119	----	----	----
Nominal	12 ga.	12 ga.	12 ga.	12 ga.	16 ga.	16 ga.	20 ga.			
Bolt Size										
*see note below	5/8 inch	5/8 inch	5/8 inch	5/8 inch	3/8 inch	5/16 inch	5/16 inch	----	----	----
Gaskets (glued in lid)	Required	Required	Required	Required	Required	Required	Required	----	----	----
Bung Openings	No	No	No	No	No	No	No	2 & ¾inch	2 & ¾inch	2 inch
Interior Lining [Ref: ¶2.10]	Clear Phenolic	Epoxy/ Phenolic	Epoxy/ Phenolic	Epoxy/ Phenolic	Clear Phenolic	Clear Phenolic	Clear Phenolic	Clear Phenolic	Clear Phenolic	Clear Phenolic

*NOTE: Counterfeit bolts, as stipulated on current DOE listing, will not be accepted. Bolts are of foreign origin.

**NOTE: Steel thickness dimensions/minimum tolerances, in millimeters, are converted from the DOT Gauge Table, CFR 49, ¶173.24, pre-HM-181 docket. [inches x 25.4000 = millimeters; current CFR 49, ¶171.10(c)(2)]

· NOTE: Minimum gauge thickness tolerances, as shown above, apply (block 1).